


TOSHIBA THYRISTOR SILICON PLANAR TYPE

SF25GZ51, SF25JZ51

MEDIUM POWER CONTROL APPLICATIONS.

- Repetitive Peak Off-State Voltage : V_{DRM}
Repetitive Peak Reverse Voltage : V_{RRM} } = 400, 600V
- Average On-State Current : $I_{T(AV)} = 25A$
- Isolation Voltage : $V_{Isol} = 1500V$ AC

Unit in mm



Weight : 5.9g

MAXIMUM RATINGS

CHARACTERISTIC		SYMBOL	RATING	UNIT
Repetitive Peak Off-State Voltage and Repetitive Peak Reverse Voltage	SF25GZ51	V_{DRM}	400	V
	SF25JZ51	V_{RRM}	600	
Non-Repetitive Peak Reverse Voltage (Non-Repetitive < 5ms, $T_j = 0 \sim 125^\circ C$)	SF25GZ51	V_{RSM}	500	V
	SF25JZ51		720	
Average On-State Current (Half Sine Waveform)		$I_{T(AV)}$	25	A
R.M.S On-State Current		$I_{T(RMS)}$	39	A
Peak One Cycle Surge On-State Current (Non-Repetitive)		I_{TSM}	350 (50Hz)	A
			385 (60Hz)	
I^2t Limit Value ($t = 1 \sim 10ms$)		I^2t	612	A^2s
Critical Rate of Rise of On-State Current (Note)		di/dt	100	$A/\mu s$
Peak Gate Power Dissipation		P_{GM}	5	W
Average Gate Power Dissipation		$P_{G(AV)}$	0.5	W
Peak Forward Gate Voltage		V_{FGM}	10	V
Peak Reverse Gate Voltage		V_{RGM}	-5	V
Peak Forward Gate Current		I_{GM}	2	A
Junction Temperature		T_j	-40~125	$^\circ C$
Storage Temperature Range		T_{stg}	-40~150	$^\circ C$
Isolation Voltage (AC, $t = 1min.$)		V_{Isol}	1500	V

Note : di/dt Test Condition, $i_G = 30mA$, $t_{GW} = 10\mu s$, $t_{gr} \leq 250ns$


961001EAA2

● TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.

ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Repetitive Peak Off-State Current and Repetitive Peak Reverse Current	I_{DRM} I_{RRM}	$V_{DRM}=V_{RRM}=\text{Rated}$	—	—	20	μA
Peak On-State Voltage	V_{TM}	$I_{TM}=80\text{A}$	—	—	1.5	V
Gate Trigger Voltage	V_{GT}	$V_D=6\text{V}, R_L=10\Omega$	—	—	1.5	V
Gate Trigger Current	I_{GT}		—	—	20	mA
Holding Current	I_H	$V_D=6\text{V}, I_{TM}=500\text{mA}$	—	—	100	mA
Critical Rate of Rise of Off-State Voltage	dv/dt	$V_{DRM}=\text{Rated}, T_c=125^\circ\text{C}$ Exponential Rise	—	50	—	$\text{V}/\mu\text{s}$
Thermal Resistance	$R_{th(j-c)}$	Junction to Case	—	—	1.3	$^\circ\text{C}/\text{W}$

MARK





NUMBER	SYMBOL		MARK
※1	TYPE	SF25GZ51	F25GZ51
		SF25JZ51	F25JZ51
※2	Lot Number Month (Starting from Alphabet A) Year (Last Number of the Christian Era)		Example 2A : January 1992 2B : February 1992 2L : December 1992

961001EAA2'




● The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.

● The information contained herein is subject to change without notice.

GATE TRIGGER CHARACTERISTIC

 $i_T - v_T$ 

SURGE ON-STATE CURRENT (NON-REPETITIVE)

 $I_H(T_c)/I_H(T_c=25^\circ C) - T_c$ (TYPICAL) $V_{GT}(T_c)/V_{GT}(T_c=25^\circ C) - T_c$ (TYPICAL) $I_{GT}(T_c)/I_{GT}(T_c=25^\circ C) - T_c$ (TYPICAL)